

# MAGIC<sup>a</sup> APPLICATIONS GUIDE

## POSPRO<sup>+</sup> 200/UNIVERSAL

### Block%ut 60RS

#### 6or Aqueous, Solvent, 5IU Solvent, Latex CD Cure Systems



MAGIC<sup>a</sup> POS PRO+ 200 OYG)(&, SORprintable, anti curl, block%ut LORthat OY specifically designed for universal printing. POS PRO+ 200 OYGcost eflectOe solution for indoor applications such GYpromotional rURB applications, trade YNlw graphics, GTJpoint%U%sale applications. POS PRO+ 200 ULers high image Wuality and durability GTJis coated witN Guniversal coating that OIUS pitable witN GWeous pigment, solvent, latex CD cure printing systems.

### PHFSICAL PROPERBI5A

Caliper &&&&&&& )(&, SOR26, microns)	Whiteness &&&&&&&&&&&
2GYOE eight &&&& 217.7 g/m <sup>2</sup>	Brightness &&&&&&&&&&&
.( 7RUYY&&&&&&&&&&&&&&	% Opacity &&&&&&&&&&&&

### APPLIC1TIONS GUIDELINES

**Imaging:** The print needs to be front imaged GTJviewed frUS the image side. The print side OYthe matte side GTJ it OYwound to the outside of the roll. Roll up signage OYthe primary product application.

**Printer Ink Compatibility:** POS PRO+ 200 OYGuniversal product that OYcompatible with aqueous, solvent, eco solvent, latex GTJCD cure printing systems. It IGT be used UTTheWlett%G kard DesignJet®, 5 VYUT Stylus PrU series, 3GTUTiPF series, GTJ most piezo thermal waterbased pigment printers. POS PRO+ 200 OYcompatible with Raster Graphics PiezoPrint -(( inks, GYwell GYRoland, Mimaki, Mutoh, Vutek, Nur, Seiko, Scitex, HP Latex CD cure printers. When using aqueous inks, it OYrecommended to use pigment inks. Although dyebased inks provide Ghigher color gamut, ink fade IGT occur. 6 or more printer compatibility, refer to the Magic Compatibility Chart under TecNTOIGR Support UT the web site.

**Printer Settings:** BU optimize print quality, printers should be set for the NQhest print quality. The maximum ink saturation level for NovaJet GTJColorSpan prints OY250%. BU minimize bleed, the recommended maximum ink saturation level OY250% UT the HP DesignJet series printerY. The meJOGeSelectOW OYdHeavy Weight Coated PGV e r d for the HP DesignJet Series printerY& CuVerdGTJ HDirectOTGGRare the printers settings for waterbased piezo wide format printers. Dry time will vary depending UTink type GTJthe ink saturation level used. BU optimize print quality UTthe Yolvent ink jet printers, 720 JVCHD direction will offer the best results. -( x +.( GRYULers MUUbutput. Optimized printer settings will vary from printer manufacturer. 25U3 to +- U3 OYGMUUstarting point for HUh pre GTJpost heaters. If available, use dryer or fix to dry image quickly.

Recommended heat settings for POS PRO UTHP Latex Printers. The print surface ULPOS PRO 200+ GTJPPOS PRO+400 OYGopaque LORthat IGT distort or warp, OYexposed to excess heat. The HP Latex printer NGYtwo heatinM adjustments. The first OY(Dry) Gdrying element designed to remove moisture from the ink GTJcontrol dot MGOGNOY element applies up to )+ deg. 6 GTJshould not GLact the POS PRO products. The second OYCure) Gcuring element. BNOSstage IGT apply up to 230b6 GTJIGT cause buckling or warping ULPOS PRO. BULOTthe correct heat setting UL the curing element turn down the cure to zero GTJthen UT the LED screen slowly JOGRup to Gtemperature where the image OYcured GYit comes ULthe printer. BNOWill help you LOTthe SOTsum temperature Then, GYthe product OY running through the machine, slowly turn the JOGR UT the LED screen until it OYcured. It OYrecommended to turn ULthe automatic cutter, when printing POS PRO +200, within GRUthe printer systems used. Some printer blades may not be able to trim this media.

**Light Stability:** Pigment inks (aqueous solvent), latex Uv Cure inks provide the best RUTerm CD fade resistance.

### FINISHING RECOMM5N4 1 TIONS

**Laminating:** Prints YNuld be completely dried before laminating. It OYrecommended to wait 24 hours before laminating to allow for adequate dry time. 3URJpressure%ensitive - SORover%aminates are recommended.

[www.sign-mart.com](http://www.sign-mart.com)

[sales@sign-mart.com](mailto:sales@sign-mart.com)

Sign-Mart  
640 N. Cypress St  
Orange, CA 92867

NATIONAL TOLL FREE

800-533-9099

IN CALIFORNIA

714-532-7100

ORDER BY FAX

714-744-0077